

BERRINGER®

PRODUCT FAMILY



TWENTY-FIVE YEARS OF PROVEN EXPERIENCE

Introduced in 1990, the **BERRINGER®** fills an important need for operators who routinely load and transport a variety of hazardous and non-hazardous material. The 1180/1820 CFM liquid ring pump options safely provide deep vacuum power and high velocity air induction with pressurized tank discharge at the push of a button. A 1600 or 2400 CFM PD blower option is also available.

The **BERRINGER®** is built to perform an impressive variety of tasks. Options might include high pressure water jetting, ASME and DOT options for highway transportation of hazardous waste, and many more flexible options to meet your requirements.



FOR MORE INFORMATION
CALL OR VISIT OUR WEBSITE
800.334.8237
KEITHHUBER.COM

Keith Huber Corporation provides a wide variety of additional features and options to address and solve your particular need. Simply give us a call at 1-800-334-8237 to discuss your requirements.

BERRINGER® FEATURES

STANDARD BERRINGER FEATURES:

- 3300 gallon (70 bbl) carbon steel tank with 5/16" shell for long life
- 20" Top manway
- Full opening hydraulically operated rear door
- Hydraulic tank lift
- PTO driven, hydraulically operated vacuum/pressure system
- 1180 CFM liquid ring vacuum pump
- Full length body trays for hose storage
- 6" discharge valve for direct pressurized or gravity unloading
- 4" intake valve for loading with internal standpipe
- Rear work lights, LED running lights
- Back-up alarm, Grounding reel
- Operator friendly push button controls
- Rear door safety prop bar
- Tank lift safety prop bar
- System controls inside a Nema 4 waterproof container



BERRINGER II OPTIONS:

- 1820 CFM liquid ring vacuum/pressure pump with deep vacuum capabilities
- Power to run the vacuum pump is provided through a splitter transfer case is mounted in line with the truck chassis main driveline
- 6" discharge and 6" intake rear door valves
- Dual self-cleaning with return to debris tank cyclones

POPULAR BERRINGER OPTIONS:

- Multiple tank capacities and configurations
- ASME and DOT 407/412
- Huber Lock™ rear door
- Stainless steel tank with wetted stainless parts
- High pressure jetting systems with integrated water compartment
- Auxiliary transfer pump
- Top-mounted hydraulically operated 6" boom with 4" hose



BERRINGER PD FEATURES:

- 3000–3500 gallon (70–83 bbl) carbon steel tank with 5/16" shell for long life
- 1600 or 2400 CFM blower with silencer
- 6" manual intake valve with internal "Y" standpipe

BERRINGER PD OPTIONS:

- Vacuum pump exhaust system with 6" camlock hose connection for "down-winding"
- Pump options – Robuschi 85 or 105 blower



Models pictured may show optional equipment. Specifications are subject to change without notice. Copyright 2016, Keith Huber Corporation, Gulfport, MS 39505

